

Universal Dry Block Low Temperature Calibrator

Portable/Benchtop

MTC 350

Measurement Capability

Precision Dry Block Calibrator with Interchangeable Thermowells

Ideal for quick / fast Site Calibration of RTDs / Bi-Metal Thermometers, Temperature Switches / Indicators etc. in Industrial & Marine Applications

High Accuracy, Resolution & Stability with Measurement Capability for mV / V / mA, Resistance TC (ISA Types J, K, R, S, N, B, T), RTD (Pt100:IEC Standard) Signals

SALIENT FEATURES

- Advanced – Micro-controller based Technology
- Heavy Duty Portable / Bench-top Model
- High Accuracy, Resolution & Stability
- Fast & heat cooling
- 128 x 64 Graphic Display
- Measurement Capability for TC, RTD, mV/mA/V & Resistance Signals
- Touch Membrane Keypad
- Switch Test Contact Measurement
- Interchangeable Single hole Thermowell Inserts
- Computer Interface & Calibration Software



SPECIFICATIONS

Range	50°C to 350°C		
Resolution	0.1°C		
Accuracy	±0.4°C		
Stability	±0.05°C		
Stabilisation Time	20 Minutes		
Temperature Readout	°C / °F Selectable		
Well Diameter	30 mm		
Immersion Depth	110 mm		
Heating Time (Ambient to max.)	20 Minutes approx.		
Cooling Time (Max. to 100°C)	33 Minutes approx.		
Switch Test facility	Provided		
Interchangeable Thermowells	Single hole to suit 1/4" & 1/2" Probes		
Housing / Mounting	Bench-top		
Power Supply	230V AC, 50 Hz		
Instrument Dimensions (L x D x H)	160 x 365 x 350 mm		
Instrument Weight (approx.)	8 Kg.		
Measurement Capability	Thermocouples	ISA Types J, K, R, S, N, B & T	Pt100 IEC Std.
	mA	0 to 25 mA	0 to 100 / 1000 mV
	Volt	0 to 10 V	Resistance 0 to 500 / 3.5 KOhm

MEASUREMENT : RANGE, RESOLUTION & ACCURACY

Type	Range	Resolution	Accuracy
mV (Low)	0 to 100	0.01	±0.05% F.S.
mV (High)	0 to 1000	0.1	±0.05% F.S.
Volts	0 to 10	0.001	±0.05% F.S.
mA	0 to 25	0.001	±0.05% F.S.
Ohms	0 to 500	0.01	±0.05% F.S.
KOhms	0 to 3.5	0.0001	±0.05% F.S.
RTD Pt100	-100 to 800	0.1	±0.05% F.S.

Type	Range	Resolution	Accuracy
TC Type J	-100 to 1200	0.1	±0.1% F.S.
TC Type K	-60 to 1260	0.1	±0.1% F.S.
TC Type R	150 to 1700	0.1	±0.1% F.S.
TC Type S	170 to 1700	0.1	±0.1% F.S.
TC Type N	0 to 1300	0.1	±0.1% F.S.
TC Type B	920 to 1820	0.1	±0.1% F.S.
TC Type T	0 to 400	0.1	±0.1% F.S.

STANDARD INCLUSIONS

- Basic Instrument
- Test Leads, Mains Cable & Spare Fuses
- Insertion Tubes (to suit 1/4" & 1/2" probes)
- Tool for Insertion Tubes
- Computer Interface
- "MTCCal" Calibration Software
- Traceable Calibration Certificate
- Instruction Manual
- Carrying Case

OPTIONAL (ADD-ON) ITEMS

- Additional Single hole Insert (Maximum 15 mm)
- Additional Thermowells / Insertion Tubes (to choose from) :
Single hole standard sizes to suit : 1/8", 1/4", 3/8", 1/2", 3/4" & 3, 4, 5, 6, 7, 8, 10, 12, 13, 15, 17, 19 & 21 mm probes
Multihole (Typical) : (1x6 + 1x8) or (3x6) or (1x10 + 1x4) mm
- Power Supply 110 VAC, 60 Hz
- Calibration Certificates are issued in Accordance with our Scope as granted by NABL per ISO/IEC 17025:2017 Standards

Manufactured by



Since 1972

NAGMAN INSTRUMENTS AND ELECTRONICS PRIVATE LIMITED

AN ISO 9001:2015 CERTIFIED COMPANY

170/1a2, Chennai Bangalore Highway Road, Sembarambakkam, Chennai – 600 123. INDIA.

Phone - Domestic Sales 044-6677 7024, 044-6677 7005 Email : mkt@chennai@nagman.com
Phone - Export Sales +91-44-6677 7025. Email : exports@nagman.com

www.nagman.com



Specifications subject to change owing to continuous development. Contact us for latest Datasheet.

NIE/TDS/MTC 350/2309/00